



Code	Type		Material	
			GB	Equiv.
BPT05	Without Inner Ring	Cylindrical Type	GCr15	SUJ2



□ D Tol.

D	Tol.
16	$\begin{smallmatrix} 0 \\ -0.008 \end{smallmatrix}$
19~30	$\begin{smallmatrix} 0 \\ -0.009 \end{smallmatrix}$
32~47	$\begin{smallmatrix} 0 \\ -0.011 \end{smallmatrix}$
52~80	$\begin{smallmatrix} 0 \\ -0.013 \end{smallmatrix}$
85~90	$\begin{smallmatrix} 0 \\ -0.015 \end{smallmatrix}$



Part Number		Seal	drf6		D	B	r	Basic Load Rating(KN)		Limit Speed (rpm)	Mass(g)
Code	No.							Cr (Dynamic)	Cor (Static)		
BPT05	5		7	$\begin{smallmatrix} +0.022 \\ +0.013 \end{smallmatrix}$	16	7.8	0.5	2.17	19.12	13440	8.9
	6		10	$\begin{smallmatrix} +0.022 \\ +0.013 \end{smallmatrix}$	19			3.33	36.4	11200	13.9
	8		12		24	9.8		4.52	47.12	8400	23.5
	10		14	$\begin{smallmatrix} +0.027 \\ +0.016 \end{smallmatrix}$	30		1	7.83	77.44	6720	42.5
	12		16		32	11.8		8.4	8.72	5600	49.5
	15		20		35			9.92	11.44	4480	50
	17		22		40		1.5	14.08	16.72	3950	90
	20	(No Seal)	25	$\begin{smallmatrix} +0.033 \\ +0.020 \end{smallmatrix}$	47	15.8		15.52	19.6	3360	135
	25		30		52			16.64	22.72	2690	152
	30		38		62		2	24.4	36.32	2240	255
	35		42	$\begin{smallmatrix} +0.041 \\ +0.025 \end{smallmatrix}$	72			25.92	40.48	1920	375
	40		50		80	19.8		28.72	43.52	1680	420
	45		55	$\begin{smallmatrix} +0.049 \\ +0.030 \end{smallmatrix}$	85		2	29.92	53.12	1500	460
	50		60	$\begin{smallmatrix} +0.049 \\ +0.030 \end{smallmatrix}$	90			31.12	57.36	1340	500

① The limit speed values in the above table apply to grease models, the limit speed of oil-lubricated models is about 160% of the above values.

② Cage the d5~d8 specifications are nylon holders, and the d8 and above specifications are steel holders.



Please Order
As Shown

Part Number		Seal	dr
Code	No.		
BPT05	5		7
	6	(No Seal)	10

BPT05—5



Discount price			
Per	1~9	10~	
Price	100%	Additional quotation	



Delivery	
	6