
## Shaft Supports T-Shaped


## **∢** Slit Type

Code	Туре	Material		Surface Treatment	Accessories				
	туре	GB	Equiv.	Surface freatment	Accessories				
GCL01 GCL02	Slit Type	15	CAEC	Black Oxide	Hex Socket Head Cap Screw 1 pc.				
GCL02	Sittiype	45	S45C	Sandblasted Electroless Nickel Plating	Hex Socket Head Cap Screw 1pc. (Stainless Steel)				

- Due to the different production batches of products, nickel plated products may have fine sand blasting, which does not affect the size and function.

  Open type, the tolerance H7 of the mounting hole D is the tolerance before the opening is processed.
- After the opening is processed, due to internal stress release, the tolerance may increase to about H8, which does not affect customer use.












Part Number		er	Н		H <sub>1</sub>	т	s	w	1.	4	Е	М	do	d <sub>1</sub>	h	N
Code	D	H7			П1	' '	5	VV	L1	d		IVI	d <sub>2</sub>	U1	h	IN
GCL01 GCL02	12	+0.018	15 20	42	H+18			17.8	7.8 30	4.5	13	M4 Through M4 Depth 8				
	13		25	54	ПТІО	10	5.8	17.0					4.5	8	4.5	
	15	0	25		H+20			29.8	42		15					1.2~2.3
	16		25 30					29.0			13					1.2~2.3
	20		20 25 30	67	H+26	- 16	7.8	34.8	8 50	6.6	18	— Mb Inrough	6.6	11	6.5	
	25	+0.021	20 25 30 40 50 60		H+28			34.6	30	0.0	21					
	30		25 30	85	H+33	20	9.8	44.8	65	9	24	M8 Depth 16	9	14	9	1.2~3.5
	35	+0.025	30 40		H+36	20					27					1.2~3.5

AUTOMATION EXPERT











GCL01-

AUTOMATIONEXPERT