



Fixed, with Dowel Hole → Economical Leveling Mounts

Heavy Load

| Code | Type | Material | Surface Treatment |
|---------|-----------------------|----------|-------------------|
| E-WAB01 | Fixed with Dowel Hole | S45C | Zinc-plated |

① Since the steel on the market has a gradient of 5mm and there are tolerances, the tolerance of the machined base -2~0mm is a reasonable range.

② This foot cup is equipped with positioning holes, which has the advantages of ensuring a more precise installation position and firm fixation etc.



The first perspective

| Part Number | | M | L | Thread Pitch | S | H | T | V | V1 | d | Load(Kg) | Reference Weight (Kg/pcs) |
|-------------|-----|----|-----|--------------|----|----|-----|----|----|----|----------|---------------------------|
| E-WAB01 | 80 | 16 | 50 | | | | | 10 | 13 | | 1700 | 0.72 |
| | | | 100 | 2 | 24 | | | | | | | 0.74 |
| | | | 150 | | | | | | | | | 0.76 |
| | | | 50 | | | | | | | | | 0.76 |
| | 80 | 20 | 100 | 2.5 | 30 | | 57 | 13 | 16 | 10 | 2000 | 0.78 |
| | | | 150 | | | | | | | | | 0.8 |
| | | | 50 | | | | | | | | | 0.8 |
| | | | 100 | 3 | 36 | | | 16 | 19 | | 2300 | 0.82 |
| | 100 | 24 | 150 | | | | | | | | | 0.84 |
| | | | 50 | | | | | | | | | 1.19 |
| | | | 100 | 2 | 24 | | | 10 | 13 | | 2400 | 1.21 |
| | | | 150 | | | | | | | | | 1.23 |
| | 100 | 20 | 200 | | | | | | | | | 1.25 |
| | | | 50 | | | | | | | | | 1.23 |
| | | | 100 | 2.5 | 30 | | 76 | 13 | 16 | | 2700 | 1.25 |
| | | | 150 | | | | | | | | | 1.27 |
| | 120 | 24 | 200 | | | | | | | | | 1.29 |
| | | | 50 | | | | | | | | | 1.27 |
| | | | 100 | | | | | | | | | 1.29 |
| | | | 150 | 3 | 36 | 20 | | 16 | 19 | | 3000 | 1.31 |
| | 120 | 20 | 200 | | | | | | | | | 1.33 |
| | | | 50 | | | | | | | | | 1.69 |
| | | | 100 | | | | | | | | | 1.71 |
| | | | 150 | 2 | 24 | | | 10 | 13 | 12 | 3000 | 1.73 |
| | 120 | 16 | 200 | | | | | | | | | 1.75 |
| | | | 250 | | | | | | | | | 1.77 |
| | | | 300 | | | | | | | | | 1.79 |
| | | | 50 | | | | | | | | | 1.75 |
| | 120 | 20 | 100 | | | | | | | | | 1.77 |
| | | | 150 | 2.5 | 30 | | 100 | 13 | 16 | | 3500 | 1.79 |
| | | | 200 | | | | | | | | | 1.81 |
| | | | 250 | | | | | | | | | 1.83 |
| | 120 | 24 | 300 | | | | | | | | | 1.85 |
| | | | 50 | | | | | | | | | 1.83 |
| | | | 100 | | | | | | | | | 1.85 |
| | | | 150 | 3 | 36 | | | 16 | 19 | | 4000 | 1.87 |
| | 120 | 24 | 200 | | | | | | | | | 1.89 |
| | | | 250 | | | | | | | | | 1.91 |
| | | | 300 | | | | | | | | | 1.93 |



| Part Number | M | L | Thread Pitch |
|-------------|-----|-----|--------------|
| E-WAB01 | 120 | 100 | 3 |

Please order
as shown

E-WAB01—D120—M24—L50



| Discount price | | |
|----------------|-----|-----|
| Per | 1~9 | 10~ |

Price 100% Additional quotation



| Delivery |
|----------|
| 2 |