




Disk Springs

Code	Type	Material		Surface Treatment	Maximum Allowable Deflection
		GB	Equiv.		
FEN02	Disk Springs	0Cr18Ni9	SUS304	—	h×75%



Applicable standards of this product: DIN 2093.



Part Number		Thickness (t)	d	at 75% deflection (h)	Total Height		Load (75% Deflection) N
Code	D				L		
FEN02	8	0.3	4.2	0.25	0.55	±0.10	104
		0.4		0.2	0.6		184
	10	0.4	5.2	0.3	0.7		184
		0.5		0.25	0.75		290
	12.5	0.5	6.2	0.35	0.85		263
		0.7		0.3	1		592
	14	0.5	7.2	0.4	0.9	246	
		0.8		0.3	1.1	713	
	16	0.6	8.2	0.45	1.05	369	
		0.9		0.35	1.25	925	
	18	0.7	9.2	0.5	1.2	510	
		1		0.4	1.4	±0.15	1146
	20	0.8	10.2	0.55	1.35	±0.10	669
		1.1		0.45	1.55	±0.15	1367
	22.5	0.8	11.2	0.65	1.45	±0.10	634
		1.25		0.5	1.75	±0.15	1543
	25	0.9	12.2	0.7	1.6	±0.10	775
		1.5		0.55	2.05	±0.15	3176
	28	1	14.2	0.8	1.8	±0.10	1014
		1.5		0.65	2.15	±0.15	3088
	31.5	1.25	16.3	0.9	2.15	±0.15	1543
		1.75		0.7	2.45		3794
	35.5	1.25	18.3	1	2.25	±0.15	1367
		2		0.8	2.8		4676
	40	1.5	20.4	1.15	2.65	±0.15	2823
		2.25		0.9	3.15		5471
	45	1.75	22.4	1.3	3.05	±0.15	3529
		2.5		1	3.5	±0.20	6927
	50	2	25.4	1.4	3.4	±0.15	4279
		3		1.1	4.1	±0.20	10766

Load is reference value.



Please order as shown

Part Number		(t)	d
Code	D		
FEN02	8	0.4	4.2
	10	0.5	5.2

FEN02-D8-t0.4



Discount price	
Per	1~49
Price	100%



Delivery	
Per	1~49
Price	100%

