

Slit

Code	Type	Material		Surface Treatment	Accessories (Hex Socket Head Cap Screw)
		GB	Equiv.		
RBT01	Slit	45	S45C	Black Oxide	TAC01
RBT02				Sandblasted Electroless Nickel Plating	TAC21
RBT06		LD30	A6061	Fine Sandblast Anodizing	TAC21
RBT11		0Cr18Ni9	SUS304	—	


Accessories(Hex Socket Head Cap Screw)

D	RBT01	RBT02/06/11
10	M4×14 1pcs	M4×14 1pcs
12	M4×14 1pcs	M4×14 1pcs
15	M5×20 1pcs	M5×20 1pcs
16	M5×20 1pcs	M5×20 1pcs
20	M5×20 2pcs	M5×20 2pcs
25	M6×25 2pcs	M6×25 2pcs
30	M8×25 2pcs	M8×25 2pcs
35	M8×25 2pcs	M8×25 2pcs
40	M8×30 2pcs	M8×30 2pcs
50	M10×35 2pcs	M10×35 2pcs



① If there is requirement of rust prevention, please choose stainless steel materials or electroless nickel-plated products firstly.

② Due to the different production batches of products, nickel plated products may have fine sand blasting, which does not affect the size and function.


D=10~16



D=20~50



Enlarged view in © Part



The first perspective

① Some models may have slit grooves in.

Part Number		D ₂	B	L	T	D ₁	F	G	b	C	S	H	Y	d	d ₁	M	h	f	e	W	
Code	D _{H7}																				
RBT01	10	50	33			30	35	18				9	5	4.5	8	M4	22	15	20		
	12	52	35	35	10	32	37	20	4.5	29		11.5							22		
	15	58	40	39		35	40	24	5.5	32		12	6	5.5	10	M5	24	17	25	1.2~2.3	
	16	58	40	39		35	40	24	5.5	32		12	6	5.5	10	M5	24	17	25	1.2~2.3	
RBT02	20	73	45	50		40	50	28	6.6	33.8	10.5	14.5	7		9.5			27	25	30	
RBT06	25	93	55	60		50	62	36		41.5	12	18.5		6.6	11	M6	34	28	35		
RBT11	30	103	65	70		60	72	42	9	47	15	21.5	10					38	34	45	
	35	108	70	80	15	65	75	45	11	55	17	24.5		9	14	M8	44	39	50		
	40	118	75	90		70	78	55		64	17	26.5	13					53	40	60	1.2~3.5
	40	118	75	90		70	78	55		64	17	26.5	13					53	40	60	1.2~3.5
	50	138	90	110	18	85	95	60	14	77.5	21.5	32.5	16	11	17.5	M10	65	48	70		


Slit Economy

Code	Type	Material		Surface Treatment	Accessories (Hex Socket Head Cap Screw)
		GB	Equiv.		
RBT51	Compact Flanged	45	S45C	Black Oxide	TAC01
RBT52				Sandblasted Electroless Nickel Plating	TAC21
RBT56		0Cr18Ni9	SUS304	—	TAC21
RBT61		Square Flanged	45	S45C	Black Oxide
RBT62	Sandblasted Electroless Nickel Plating				TAC21
RBT66	0Cr18Ni9		SUS304	—	TAC21


① If there is requirement of rust prevention, please choose stainless steel materials or electroless nickel-plated products firstly.

② Due to the different production batches of products, nickel plated products may have fine sand blasting, which does not affect the size and function.


D=10~15




D=20~50



RBT51/52/56



RBT61/62/66



The first perspective

Part Number		D ₂	B	L	T	D ₁	F	G	b	C	S	H	Y	W	d	d ₁	M	h	f	e	K	P.C.D	
Code	D _{H7}																						
Compact Flanged	10	45	27	35	10	26	30	18	4.5	29		9.5	3		4.5	8	M4	22	15	14	35	36	
	12	50	31			30	34	22				10.5	3.5						16	38	40		
	15	58	37	39		35	38	26	5.5	32		12.5	4	1.2~2.3	5.5	9.5	M5	24	17	19	44	46	
	20	64	41	50	12	40	42	30	6.6	33.8	10.5	14	6.5		6.6	11	M6	27	25	24	50	52	
Square Flanged	25	80	49	60		48	54	35		41.5	12	17						34	28	29	62	64	
	30	90	59	70		58	58	45	9	47	15	21	8					38	34	34	68	74	
	35	100	65	80	15	64	66	48		55	16	23			9	14	M8	44	39	41	76	82	
	40	106	71	90		70	70	54	11	64	17	26	11.5	1.2~3.5					53	40	46	80	88
	40	106	71	90		70	70	54		64	17	26	11.5	1.2~3.5					53	40	46	80	88
	50	125	87	110	18	85	80	68	14	77.5	21	32	12		11	17.5	M10	65	48	58	94	105	

① The tolerance and perpendicularity of D_{H7} is before slitting. ② Recommended tolerances of fitting shafts: g6, f8.

Slit

Part Number	D _{H7}	D ₂
RBT01	<10	50
RBT02	12	52
RBT02 - D10	15	58

Slit Economy

Part Number	D _{H7}	D ₂
RBT51	<10	45
RBT52	12	50
RBT52 - D10	15	58



Discount price	Per	1~4	5~
Price	100%	Additional quotation	



Delivery
6