



Code	Type	Thread	Material		Surface Treatment
			GB	Equiv.	
TBK11	Domed Nut	Coarse	0Cr18Ni9	SUS304	—



① Applicable Standards: DIN 1587-1987

② Hexagon nut section and the dome section are welded together.



The first perspective

Part Number		P Pitch	m		h		S		D (max)	T (min)	e(Approx.)	SR(Approx.)
Code	M		max	min	max	min	max	min				
TBK11	3	0.5	6.2	5.7	2.8	2.2	5.5	5.3	4.9		5.9	3
	4	0.7	8	7.64	3.7	3.2	7	6.78	6.5		7.66	3.25
	5	0.8	10	9.64	4.7	4	8	7.78	7.5	2	8.79	3.75
	6	1.0	12	11.57	6.14	5	10	9.78	9.5		11.05	4.75
	8	1.25	15	14.57	7.64	6.5	13	12.73	12.5		14.38	6.25
	10	1.5	18	17.57	9.64	8	17	16.73	16		18.9	8
	12	1.75	22	21.48	10.3	10	19	18.67	18	3	21.1	9
	16	2.0	28	27.48	12.3	13	24	23.67	23	4	26.75	11.5
	20	2.5	34	33.38	14.9	16	30	29.67	28	5	33.53	14
	24	3.0	42	41.38	17.7	19	36	35.38	34	6	39.98	17



Please order as shown

Part Number	P
Code M Pitch	
3 0.5	
4 0.7	
5 0.8	

TBK11—M3



● Discount price

Per 1~99 100~
Price 100% Additional quotation



Delivery

8