


Fixed • Metal + Rubber Base ▶ Medium Load

Antivibration Leveling Mounts

Code	Type	Material		Hardness	Surface Treatment	
		Bottom Shell	Bolt		Bottom Shell	Bolt
WAK02	Metal + Rubber Base	SPCC	S45C	Nitrile Rubber (NBR)	Shore A70~75	Zinc-plated
WAK06		SUS304	SUS304			

Features

- Good shockproof performance.
- The shaft is a integrated processing type, with excellent coaxial resistance and impact resistance.



The first perspective

Part Number		M	L	Thread Pitch	S	H	V	V ₁	Load (Kg)	Reference Weight (Kg/pcs)
Code	D									
WAK02 WAK06	40	10	50	1.5	17		7	8	200	0.09
			75							0.11
			100							0.13
		12	50	1.75	19	19	8	10	300	0.12
			75							0.15
			100							0.16
	60	12	125	1.75	19	21	8	10	300	0.17
			150							0.19
			50	2	24		10	13	500	0.19
		16	75							0.22
			100							0.24
			125							0.25
	80	12	150	1.75	19	23	8	10	300	0.27
			50							0.27
		16	75		2		10	13	500	0.3
			100							0.33
			125							0.36
		16	150	2	24		10	13	500	0.41
			50							0.2
			75							0.23
		12	100	1.75	19		8	10	300	0.25
			125							0.27
			150							0.29
		16	50	2	24		10	13	500	0.29
			75							0.31
			100							0.33
		16	125	2						0.35
			150							0.38



Please order as shown

Part Number		M	L	Thread Pitch
Code	D			
WAK02	40	10	75	2
WAK06	60	16	100	2

WAK02—D80—M16—L75



Discount price

Per	1~9	10~
Price	100%	Additional quotation



Delivery

2

Bearing capacity test (Test Part Number : WAK02-D80-M16-L100)

