

# Single-Layer Tower Lamps

## Small Type

Lampshade Diameter Ø50


Code	Type	Lampshade Diameter
ZHD25	Small Type	Ø50

### Features


- High cost performance;
- Product service life is more than three years;
- Nut installing is easy to use and has strong stability;
- It has three color(Red, yellow, green)warning function;
- The optical patterns on the outside of the lampshade make the light uniform.




B(Always-on)  
D(Full-Flash)



F(Always-on With Beep)



### Wiring Diagram



The first perspective

Part Number		Mounting Method	Function	Color	Lampshade Diameter(Ø)	Rated voltage	Wiring Method	IP Rating
Code	Number of Layers							
ZHD25	1(1 Layer)	C(Rod Disc Type)	B(Always-on) D(Full-Flash) F(Always-on With Beep)	RYG (Red Yellow Green)	50	DC24V	Direct Power Input Type (Common Positive/ Negative Universal)	IP65

### Environmental Requirements

Operating Temperature	-20~45°C
Storage Temperature	-40~70°C
Operating Humidity	10~90%
Storage Humidity	10~90%

### Basic Parameters

Input Voltage	DC24V
Wire Length	About 0.5M
Light	SMD 2835 LED 0.2W/PCS
Lamp Life	The light life is 100,000 hours, and the whole lamp life is 50,000 hours
Exterior Design	The lamp body is black, the lampshade is translucent, and the appearance of fine fire pattern
Outgoing Light Angle	360° visibility of the whole light



Please order as shown

Part Number		Mounting Method	Function	Color
Code	Number of Layers			
ZHD25	1(1 Layer)	C(Rod Disc Type)	B D	RYG (Red Yellow Green)

ZHD25—1—C—B—RYG