


Single Core Wires

◀ RV Single Core Wire

Code	Type	Insulator Material
ZIE57	RV Single Core Wire	PVC

3C



Feature

- It is made of multiple high-purity 4N anaerobic twisted wire, which is soft, anti-bending and swinging, and has a conductivity of 99.99%. It has superconducting properties, reduces resistance and heat generation, and more stable transmission performance.


Application

- Suitable for home decoration lighting, switch plug, air-conditioning wiring, equipment control wiring, cabinet electronic equipment and other connections.



PVC Insulator

Copper Core Conductor




PVC Insulator

Conductor

RV Copper Core PVC-Insulator Flexible Cable

Sell by	Length Per Roll
Roll	100m/Roll



The first perspective

Part Number		Color	Length(m)	Conductor Structure (Piece/mm)	Insulation Outer Diameter(mm)
Code	Cross-Sectional Area (mm ²)				
ZIE57	0.3			16/0.15	2
	0.5	R(Red) BE(Blue)		28/0.15	2.15
	0.75	BK(Black) LB(Light Blue)		24/0.2	2.35
	1	W(White) Y(Yellow)		32/0.2	2.5
	1.5	GN(Green) O(Orange)	100	30/0.25	3
	2.5	BR(Brown) H(Grey)	(Sell by Roll 100m/Roll)	49/0.25	3.65
	4	YG(Yellow-Green)		56/0.3	4.3
	6			84/0.3	4.9
	10	R(Red) BK(Black)		Single Copper	6.1
	16			Wire ≥ 0.41mm	7.1

Technical Parameters

Rated Voltage	450/750V
Operating Temperature	70°C
Standards Compliant	GB5023.X-2008
Flammability Rating	VW-1Standard



Please order as shown

Part Number		Color	Length(m)
Code	Cross-Sectional Area(mm ²)		
ZIE57	0.75	R(Red)	100(Sell by Roll 100m/Roll)
	1	BE(Blue)	

ZIE57-0.75-R-100