


Flexible Drag Chain Cables

Double-Twisted Shielded Signal Cable, 5 Million Times


Code	Type	Shield	Insulator	Sleeve	Oil Resistant	Color
ZLK23	Signal Cable	Double Twisted Shield	PVC	PVC	Slight Oil Resistant	Black

Application:
Flexible data cables for the transmission of analog and digital signals in equipment with a control processor, or as a connection between an instrument and a control equipment.



Sell by	Length Per Roll
Roll	100m/Roll

Conductor: multiple pieces of 0.1 tinned annealed copper wire twisted structure



The first perspective

Part Number		Cross-Sectional Area	Length	Number of Cores×Cross	20°C Conductor	Cable Outer Diameter
Code	Number of Cores	(mm ²)	(m)	-Sectional Area(mm ²)	DC Resistance	(mm)
ZLK23	1P(2)	0.14	100 (Sell by Roll 100m/Roll)	1P×0.14	150	3.9
	2P(4)			2P×0.14		5.5
	7P(14)			7P×0.14		7.8
	1P(2)	0.2		1P×0.2	95	4.2
	2P(4)			2P×0.2		6.0
	3P(6)			3P×0.2		6.4
	4P(8)	0.2		4P×0.2	95	7.0
	5P(10)			5P×0.2		7.5
	6P(12)			6P×0.2		8.2
	7P(14)	0.3		7P×0.2	71.2	8.5
	1P(2)			1P×0.3		4.6
	2P(4)			2P×0.3		6.2
	3P(6)	0.3		3P×0.3	71.2	6.6
	4P(8)			4P×0.3		7.5
	5P(10)			5P×0.3		7.8

Core Wire Color Identification

No.	Color	
1P	Red	Red and White
2P	Blue	Blue and Black
3P	Black	Black and White
4P	Green	Green and Black
5P	Yellow	Yellow and Black
6P	Orange	Orange and Black
7P	Brown	Brown and Black

Technical Parameters

Movement Lifespan	Over 5 Million Times
Rated Voltage	300V
Test Voltage	1.5KV
Bending Radius	7.5×OD
Operating Temperature	-20 ~ +80°C
Standards	CE
Flammability Rating	VW-1



Please order as shown

Part Number		Cross-Sectional Area(mm ²)	Length(m)
Code	Number of Cores		
ZLK23	2P	0.14	100
	3P		(Sell by Roll 100m/Roll)

ZLK23 - 2P - 0.14 - 100

怡合达
AUTOMATION EXPERT