
Long Timing Belts

◄ Glass Cord

No. of Teeth Configurable Joint Machining

	Code	Туре			Operating Temp.		
l	Code			①Main Body	@Core Wire	③ Cloth	Operating remp
l	ECX25	Made in	Standard			_	4
l	ECX27		Backside Cloth Lined	Polyurethane	Glass Cord	Nylon Cloth	-20~70°C
l	ECX28	China	Both Sides Cloth Lined			Nyion Cioui	



[] The belt of steel core shall not be tensioned from the back, otherwise the core wire will break.

[] Polyurethane open end belts is made of thermoplastic polyurethane material, which has high wear resistance

1 Strengthening the core wire can ensure that it still maintains good movement ability in rotation, reliable transmission and stable size.

¶ Reduces friction coefficient of conveyed items and is suitable for accumulation conveyance. Reduces friction coefficient between conveyed materials and pulleys and cuts noise.

Belt length tolerance :0~2 pitch.

The working conditions of coaxial pairing need to be explained clearly. For example, the usage of 2pcs coaxial timing belts requires remark: ECX25-SSM-100-45 (2pcs per pair) total 10 sets. The number of the matching belts is related to the width, and some specifications cannot be matched for production.

① Core trunking in the slitting part of the timing belt is a normal craft. If there's any special need, please note: ECX25-S5M-100-450 (original side). Due to the customization, delivery time should be extended correspondingly



±0.8

Belt nominal width tolerance

Belt nominal width(mm) tolerance


3~30 ±0.5

31~50

Joint Machining Part


Standard ECX25

Belt Type: L/H/T5/T10



Standard ECX25

Belt Type: S5M/S8M




Backside Cloth Lined

ECX27



Both Sides Cloth Lined

FCX28



Part Number			Number of Teeth	Color Tone		Belt Width	Allowable Tension
Code	Belt Type	Belt Nominal Width	nvullibel of feetil	ECX25	ECX27/28	(mm)	(N)
		050				12.7	90
	L	075	80~1500			19.1	140
		100				25.4	185
		150				38.1	275
		075				19.1	165
	н	100	60~1000			25.4	215
	п	150	00~1000			38.1	325
		200				50.8	430
		100				10	60
Standard	S5M	150	150~2000	Not		15	90
ECX25		250		specified	Not	25	150
Dankaida Clath Linad		150		(Milky	specified	15	115
Backside Cloth Lined ECX27	S8M	250	90~1500	White)	(Milky White)	25	195
LUXZI	SOW	300				30	235
Both Sides Cloth Lined		400		В	Villicey	40	315
ECX28	Т5	100		(Black)		10	57
		150	150~2000			15	86
	13	200	130~2000			20	115
		250			37	25	144
		150			進	15	179
		200				20	239
	T10	250	80~1500			25	299
		300		, it		30	359
		400		197		40	480
		500				50	600

Overall Length=Number of Teeth×Pitch.

Code	Belt Type	Pitch P	2θ	L(Lr)	h	H	V	Ra
	L	9.525	40°	3.2	1.9	3.7	1.8	\\\
	H	12.7	40°	4.4	2.29	4.5	2.21	_
ECX25 ECX27	T5	5	40°	1.8	1.2	2.3	1.1	_
ECX27	T10	10	40°	3.5	2.5	4.7	2.2	_
LOXLO	S5M	5	_	3.25	1.91	3.6	1.69	3.25
	S8M	8	_	5.2	3.05	5.3	2.25	5.2



			Number	Number of Teeth	Color Tone	
_	Code	Belt Type	Belt Nominal Width	Number of feetif		
₽	ECX26	Θ	Q50		Not specified	
			075	80~1500	(Milky White)	
			100		(Black)	





ECX25-L-050-80-B