





Lining Thickness Fixed ▶ Straight(with Lining)

Rollers



Code	Type	Material			Surface Treatment	Hardness
		Core	Lining	Bearing		
QAC22	Straight	SUS304	Urethane (Natural Color)	Steel		Shore A95
QAC23				Stainless Steel		Shore A90
QAC24			Silicon Rubber (Light Gray)			Shore A70
QAC25						Shore A50
QAC26						Shore A60
QAC27		A5052	Urethane (Natural Color)	Steel		Shore A95
QAC28						Shore A90
QAC42			Silicon Rubber (Light Gray)			Shore A70
QAC43						Shore A50
QAC44						Shore A60
QAC45			NBR(Black)			
QAC46						
QAC47						
QAC48						

① Urethane may discolor over time, but there is no effect on physical properties.



The first perspective

Part Number		L	D	d	D1(H7)	d1	S	Use Bearings
Code	No.							
QAC22	QAC42	20	20	6	10	8	3	676ZZ×2
QAC23	QAC43	25	25	6	15	9.8	5	696ZZ×2
QAC24	QAC44	30	30	8	19	14.8	6	698ZZ×2
QAC25	QAC45	35A	35	8	22	17.8	7	608ZZ×2
QAC26	QAC46	35	35	10	26	17.8	6	6900ZZ×2
QAC27	QAC47	40A	40	10	26	17.8	8	6000ZZ×2
QAC28	QAC48	40	40	12	28	23.8	8	6001ZZ×2
		50A	50	12	32	23.8	10	6201ZZ×2
		50	50	15	32	27.8	9	6002ZZ×2

① When No. 50A and L=20, the corresponding value of S is 8, and the applicable bearing is 6001ZZ×2.



Optional Processing

Code	Spec.
EP	Change to Black Anti-static Urethane Ordering Code: EP ① Change ordinary urethane to anti-static urethane. ② Surface resistance values of polyurethane with hardness Shore A90 and Shore A70 are $10^5 \sim 10^8 \Omega \cdot M$. ③ Surface resistance value of polyurethane with hardness of Shore A50 is $10^5 \sim 10^8 \Omega \cdot M$.

① Optional processing is only applicable to codes that lining material is urethane.



Please order as shown

Part Number		L	D
Code	No.		
QAC22	30	20 25 30 40 50	30
QAC23	35A	25 30 40 50	35

QAC23—35A—L30

Optional Processing

Part Number		L	Optional Processing Code
Code	No.		
QAC22	30	20 25 30 40 50	EP
QAC23	35A	25 30 40 50	

QAC23—35A—L30—EP



Discount price			
Per	1~9	10~	
Price	100%	Additional quotation	



Delivery

8