





Code	Type	Material	Hardness(Shore)	Color	Operating Temp.Range	Applications
XTF01	S Series	Nitrile Rubber	HA65 ⁺¹⁰ ₋₀	Black	-20~100°C	Mineral Oil Resistant
XTF02			HA85 ⁺¹⁰ ₋₀		-15~100°C	
XTF11		Silicon Rubber	HA45 ⁺¹⁰ ₋₀	Milky White	-40~200°C	Heat Resistant
XTF12			HA65 ⁺¹⁰ ₋₀	Reddish Brown		
XTF21		Fluoro Rubber	HA85 ⁺¹⁰ ₋₀	Black	-10~200°C	
XTF22	G Series	Nitrile Rubber	HA65 ⁺¹⁰ ₋₀	Black	-20~100°C	Mineral Oil Resistant
XTH01			HA85 ⁺¹⁰ ₋₀		-15~100°C	
XTH11		Silicon Rubber	HA45 ⁺¹⁰ ₋₀	Milky White	-40~200°C	Heat Resistant
XTH12			HA65 ⁺¹⁰ ₋₀	Reddish Brown		
XTH21		Fluoro Rubber	HA65 ⁺¹⁰ ₋₀	Black	-10~200°C	



0.1 or less
① Enlarged Cross Section

Execution Standard: JIS B 2401



S Series

Part Number		Nominal Number	d ₂	Inner Diameter				Matching Dimension	
Code	No.			d ₁	XTF01 XTF02	XTF11 XTF12	XTF21 XTF22	d ₁	D
XTF01 XTF02 XTF11 XTF12 XTF21 XTF22	3	3	1.5±0.09	2.5				3	5
	4	4		3.5				4	6
	5	5		4.5				5	7
	6	6		5.5				6	8
	7	7		6.5				7	9
	8	8		7.5				8	10
	9	9		8.5				9	11
	10	10		9.5				10	12
	11.2	11.2		10.7				11.2	13.2
	12	12		11.5				12	14
	12.5	12.5	2.0±0.09	12.0				12.5	14.5
	14	14		13.5				14	16
	15	15		14.5				15	17
	16	16		15.5				16	18
	18	18		17.5				18	20
	20	20		19.5				20	22
	22	22		21.5	±0.14	±0.44	±0.29	22	24
	22.4	22.4		21.9				22.4	25.4
	24	24		23.5				24	27
	25	25		24.5				25	28
	26	26		25.5				26	29
	28	28		27.5				28	31
	29	29		28.5				29	32
	30	30		29.5				30	33
	31.5	31.5	2.0±0.09	31.0				31.5	34.5
	32	32		31.5				32	35
	34	34		33.5				34	37
	35	35		34.5				35	37
	35.5	35.5		35.0				35.5	38.5
	36	36		35.5				36	39
	38	38		37.5				38	41
	39	39		38.5				39	42
	40	40		39.5				40	43
	42	42		41.5				42	45
	44	44	2.0±0.09	43.5				44	47
	45	45		44.5				45	48
	46	46		45.5	±0.24	±0.74	±0.49	46	49
	48	48		47.5				48	51
	50	50		49.5				50	53

G Series (AS568)

Part Number		Nominal Number	d ₂	Inner Diameter				Matching Dimension	
Code	No.			d ₁	XTH01 XTH02	XTH11 XTH12	XTH21	d ₁	D
XTH01 XTH02 XTH11 XTH12 XTH21	25	G25	3.1±0.09	24.4	±0.24	±0.37	±0.29	25	30
	30	G30		29.4	±0.28	±0.43	±0.34	30	35
	35	G35		34.4	±0.32	±0.49	±0.39	35	40
	40	G40		39.4	±0.36	±0.55	±0.44	40	45
	45	G45		44.4	±0.40	±0.61	±0.49	45	50
	50	G50		49.4	±0.44	±0.67	±0.53	50	55
	55	G55		54.4	±0.48	±0.73	±0.58	55	60
	60	G60		59.4	±0.52	±0.79	±0.63	60	65
	65	G65		64.4	±0.56	±0.85	±0.68	65	70
	70	G70		69.4	±0.60	±0.91	±0.73	70	75
	75	G75	5.7±0.09	74.4	±0.64	±0.97	±0.77	75	80
	80	G80		79.4	±0.68	±1.03	±0.82	80	85
	105	G105		104.4	±0.86		±0.86	105	110
	120	G120		119.4	±0.97		±0.97	120	125
	145	G145		144.4	±1.15		±1.15	145	150
	170	G170		169.3	±1.32		±1.32	170	180

G Series (AS568)

Part Number	Code	No.	Nominal Number
XTH01	Code	25	G25
XTH02	Code	30	G30
XTH01—25			



Discount price
Per 1~49 50~
Price 100% Additional quotation



Delivery
6